

6-GFMHR

High Rate Battery


6-GFMHR-700XW



Benefits

- ▶ High rate, can be used in the standby power which less than 15min
- ▶ High consistency, security, reliability and stability
- ▶ Fast charging speed, low self-discharge rate
- ▶ Designed life is 15 years
- ▶ Good anti-high current performance
- ▶ Good anti-over-discharge performance
- ▶ Excellent anti-overcharge performance
- ▶ Good anti-impact performance
- ▶ Excellent anti-vibration performance

Dimensions



Technical Parameters

Nominal Voltage	12 V
Rated Power	700W,15min to 1.67V/cell(25°C)
Weight	60kg(132.27 lbs)
Dimensions	Length: 559 mm (22.01 in) Width: 125 mm (4.92 in) Height: 315 mm (12.40 in)
Internal Resistance (full charged)	2.80 mΩ
Short- circuit Current	2684 A
Self Discharge C ₁₀ @25°C(77°F)	Less than 8% after 90 days storage
Operating Temperature Range	Discharge: -40°C ~ 50°C(-40°F ~ 122°F) Charge: -20°C ~ 45°C(-4°F ~ 113°F) Storage:-20°C ~ 40°C(-4°F ~ 104°F)
Recommended Operating Temperature	15°C ~ 25°C (59°F ~ 77°F)
Recommended Charging Current	27 A
Charging Voltage @25°C(77°F)	Float: 2.23 V/cell Equalize: 2.35 V/cell
Terminal	M8
Container Materials	ABS/ABS V0 (Optional)
Capacity Affected by Temperature(C ₁₀)	105% @ 40°C(104°F) 85% @ 0°C(32°F) 60% @ -20°C(-4°F)
Design Life @25°C(77°F)	15 years

Certification

- ISO 9001
- ISO 14001
- GB/T 28001
- UL
- CE

Technical Features

- ▶ Double-sided smear, cast welding and other processes strengthen the process control and improve battery consistency
- ▶ High-strength ABS material and patented sealing technology ensure the normal use of the battery without leakage, expansion and rupture
- ▶ Corrosion-resistant alloy greatly extend the battery life

6-GFMHR

High Rate Battery

6-GFMHR-700XW







Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

F.V/Time	5min	10min	15min	20min	25min	30min	1hr	1.5hr	2hr	3hr	6hr	10hr
1.60V	495	370	351	277	237	213	108.9	83.3	72.4	52.2	30.1	18.9
1.67V	474	361	348	275	228	209	106.8	82.1	71.2	51.4	29.9	18.7
1.70V	463	356	345	273	221	203	106.0	80.9	69.6	50.4	29.8	18.5
1.75V	417	351	323	255	208	194	99.0	77.4	68.4	48.6	29.2	18.3
1.80V	385	342	300	237	190	168	97.0	76.3	67.5	45.0	29.1	18.0
1.85V	365	323	273	215	172	157	89.5	72.1	65.4	44.6	27.7	17.8

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

F.V/Time	5min	10min	15min	20min	25min	30min	1hr	1.5hr	2hr	3hr	6hr	10hr
1.60V	903	810	710	530	470	415	208.0	175.1	141.1	109.1	61.4	37.6
1.67V	877	800	700	526	465	411	204.6	172.5	139.2	107.3	61.1	37.4
1.70V	853	780	680	524	463	408	202.8	170.2	137.1	105.4	59.4	36.4
1.75V	794	730	660	520	460	400	200.2	166.9	136.4	102.3	59.3	36.3
1.80V	746	679	607	431	392	354	194.9	166.1	135.2	95.4	59.1	36.0
1.85V	710	620	550	401	368	335	182.4	160.3	133.3	93.5	57.8	35.4

Performance Curve



*Declaration:

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact CHINASHOTO for the latest information.

Welcome to Visit : www.chinashoto.com