

Shoto HP-S10~25



01

IP21

02

High Voltage (High System Efficiency)

03

Pile Up Design (Wireless Connection Easy to install)

04

Wide Compatibility
(Matching with Leading Inverter Brands)

05

Self (Automation Configuration)



Technical Parameters

	HP-S10	HP-S15	HP-S20	HP-S25
Battery module	HP - S05 (5.12 kWh)			
	2 module	3 module	4 module	5 module
Usable Energy	10.24 kWh	15.36 kWh	20.48 kWh	25.6 kWh
Nominal Voltage	204.8 V	307.2 V	409.6 V	512.0 V
Operating Voltage Range	160 ~ 233.6 V	240 ~ 350.4 V	320 ~ 467.2 V	400 ~ 584 V
Communication	CAN			
Dimensions (W/D/H)	600 x 390 x 625 mm	600 x 390 x 825 mm	600 x 390 x 1025 mm	600 x 390 x 1225 mm
Weight	126 ± 2 kg	179 ± 3 kg	232 ± 4 kg	285 ± 5 kg
Protection Level	IP21			
Operating Temperature	Charge: 0 to +50 Discharge: -20 to +55			
Certification	UL1973 / IEC62619 / CE-EMC / UN38.3			
Warranty	10 years			

